


AD-A225 263



by

P.I. Potaturkin, P. Ye. Tverdokhlebov, Yu. V. Chuguy



Approved for public release;
Distribution unlimited.

HUMAN TRANSLATION

FTD-ID(RS)T-0326-90 5 June 1990

MICROFICHE NR: FTD-90-C-0006571

PATTERN RECOGNITION METHOD

By: P.I. Potaturkin, P. Ye. Tverdokhlebov,
Yu. V. Chuguy

English pages: 3

Source: USSR Patent Nr. 456282, 21 December 1972,
pp. 1-2

Country of origin: USSR
Translated by: Carol S. Nack
Requester: FTD/TTTRE/J.M. Finley

Approved for public release;
Distribution unlimited.

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION

PREPARED BY:

TRANSLATION DIVISION
FOREIGN TECHNOLOGY DIVISION
WPAFB OHIO

U. S. BOARD ON GEOGRAPHIC NAMES transliteration SYSTEM

Block	Italic	Transliteration	Block	Italic	Transliteration
А а	А а	A, a	Р р	Р р	R, r
Б б	Б б	B, b	С с	С с	S, s
В в	В в	V, v	Т т	Т т	T, t
Г г	Г г	G, g	У у	У у	U, u
Д д	Д д	D, d	Ф ф	Ф ф	F, f
Е е	Е е	Ye, ye; E, e*	Х х	Х х	Kh, kh
Ж ж	Ж ж	Zh, zh	Ц ц	Ц ц	Ts, ts
З з	З з	Z, z	Ч ч	Ч ч	Ch, ch
И и	И и	I, i	Ш ш	Ш ш	Sh, sh
Й й	Й й	Y, y	Щ щ	Щ щ	Shch, shch
К к	К к	K, k	Ъ ъ	Ъ ъ	"
Л л	Л л	L, l	Ы ы	Ы ы	Y, y
М м	М м	M, m	Ь ь	Ь ь	'
Н н	Н н	N, n	Э э	Э э	E, e
О о	О о	O, o	Ю ю	Ю ю	Yu, yu
П п	П п	P, p	Я я	Я я	Ya, ya

*ye initially, after vowels, and after ъ, ь; e elsewhere.
When written as ѣ in Russian, transliterate as yě or ě.

RUSSIAN AND ENGLISH TRIGONOMETRIC FUNCTIONS

Russian	English	Russian	English	Russian	English
sin	sin	sh	sinh	arc sh	sinh ⁻¹
cos	cos	ch	cosh	arc ch	cosh ⁻¹
tg	tan	th	tanh	arc th	tanh ⁻¹
ctg	cot	cth	coth	arc cth	coth ⁻¹
sec	sec	sch	sech	arc sch	sech ⁻¹
cosec	csc	csch	csch	arc csch	csch ⁻¹

Russian English

rot curl
lg log

GRAPHICS DISCLAIMER

All figures, graphics, tables, equations, etc. merged into this translation were extracted from the best quality copy available.



Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution	
Availability Codes	
Dist	Avail and/or Special
A-1	

PATTERN RECOGNITION METHOD

O. I. Potaturkin, P. Ye. Tverdokhlebov, Yu. V. Chuguy

Institute of Automatics and Electrometry of the
Siberian Branch of the Academy of Sciences USSR

The invention pertains to computer technology and can be used in devices for optical data processing designed to solve problems of pattern recognition.

The known method of pattern recognition is based on passing a light beam through two half-tone transparencies with the subsequent integration of the light flux. The transmission law for the intensity of the first transparency corresponds to one of the functions used to determine the signs, and the transmission law of the second - to the pattern that is to be recognized. In this case, the transparencies are arranged so that the pattern of the first transparency is projected by the optical system onto the plane of the second.

The inadequate precision of this method of recognition results from the difficulty of modulating the light fluxes in proportion to the dispersion functions.

The purpose of the invention is to increase the precision of recognition.

To do this, the light flux is modulated according to the dispersion function on the X -axis, it is integrated on this same axis, and it is modulated according to the dispersion function on the Y -axis.

The figure shows a version of the device that implements this method.




Figure.

The device contains incoherent light source 1, transparency 2 with a silhouette image of the one-dimensional component of the dispersion function on the X -axis, spherical lens 3, cylindrical lens 4, the transparency with the pattern to be recognized 5, spherical lens 6, cylindrical lens 7, the transparency with the silhouette image of the one-dimensional component of the dispersion function on the Y -axis 8, and photodetector 9.

With incoherent illumination, the spherical lens 3 together with the cylindrical lens 4 project the light flux modulated by transparency 2 in plane 5 onto the X -axis, and the defocused light flux - onto the Y -axis. Consequently, the silhouette image of the one-dimensional component of the dispersion function is transformed into a light "band" with an intensity that varies along the X -axis in proportion to this component, but is constant along the Y -axis. Spherical lens 6 together with cylindrical lens 7 project the light flux modulated by transparency 5 in plane 8 onto the Y -axis, while defocusing occurs on the X -axis. This makes it possible to obtain a light "band" in plane 8 with an intensity that varies along the Y -axis in proportion to the result of the integration of the product of the pattern being recognized and the original component with respect to argument X , but is constant along the X -axis. The light flux

that passes through transparency 8, proportional to the value of the corresponding spectral component, is integrated and subtracted by the photodetector 9.

Invention Claim

A method of pattern recognition consisting in the modulation of a light flux with subsequent integration *that is different* because in order to increase the precision of recognition, the light flux is modulated according to the dispersion function on the X-axis, it is integrated on this same axis, and it is modulated according to the dispersion function on the Y-axis.

DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

<u>ORGANIZATION</u>	<u>MICROFICHE</u>
C509 BALLISTIC RES LAB	1
C510 R&T LABS/AVEADCOM	1
C513 ARRADCOM	1
C535 AVRADCOM/TSARCOM	1
C539 TRASANA	1
Q591 FSTC	4
Q619 MSIC REDSTONE	1
Q008 NTIC	1
E053 HQ USAF/INET	1
E404 AEDC/DOF	1
E408 AFWL	1
E410 AD/IND	1
F429 SD/IND	1
P005 DOE/ISA/DDI	1
P050 CIA/OCR/ADD/SD	2
AFTT/LDE	1
NOIC/OIC-9	1
CCV	1
MIA/PHS	1
LLYL/CODE L-309	1
NASA/NST-44	1
NSA/T513/TDL	2
ASD/FTD/TTIA	1
FSL	1